Projects: M280 Date: March 25, 2013 By: YC

## 1. Configure the device driver.

🛯 🍑 M280_Driver	• W2K -> Windows 2000
⊿ 鷆 w2k	- x86 : 32bit
鷆 x86	Wxp -> Window Xp
4 퉲 wih	- x64 : 64bit
ル хб4	- x86 : 32bit
鷆 x86	<ul> <li>Wlh -&gt; Vista , Window 7 and Windows 8</li> </ul>
a 🌗 wxb	- x64 : 64bit
鷆 хб4	- x86 : 32bit
📗 x86	

## 2. Install Driver

- 1. Connect M280 to PC with USB cable.
- 2. Open the Device Manager

Evice Manager	
File Action View Help	
<ul> <li>Young-PC</li> <li>Computer</li> <li>Disk drives</li> <li>Display adapters</li> <li>DVD/CD-ROM drives</li> <li>Human Interface Devices</li> <li>Human Interface Devices</li> <li>HEEE 1394 Bus host controllers</li> <li>Keyboards</li> <li>Mice and other pointing devices</li> <li>Monitors</li> <li>Network adapters</li> <li>Other devices</li> <li>Mathematical Devices</li> <li>Other devices</li> <li>Portable Devices</li> <li>Portable Devices</li> <li>Portable Devices</li> <li>Will SB-to-Serial Comm Port (COM8)</li> <li>Will SB Serial Port (COM21)</li> <li>Processors</li> <li>Sound, video and game controllers</li> <li>Storage controllers</li> </ul>	

3. Please follow these steps.



## 3. Check if the device driver is installed properly

🚽 Device Manager				
File Action View Help				
Image: Second	M280 USB Driver (3.4.7.000) Properties			
USB Root Hub USB Root Hub USB Root Hub USB Root Hub USB Root Hub	OK Cancel			